

Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5

## Add a Command --300




Fig. 6




Fig. 7

	450	
	<b>≝</b> Edit Parameter	×
451	Command Node: command3	
	No keyword (implied type)	
452	Parameter <u>K</u> eyword:	(unnamed2)
453	Parameter <u>Type:</u>	unsigned long
454	<u>Sub</u> Range:	Min: 0 Max: 4294967295
455	Agray Parameter	Min: Max:
456	Custom Handler Validator:	
457	Automatic convert to native type in handler	
458	Default Value:	
459	Access:	I COMPANY IN
460	Set <u>R</u> apidMark:	adminEMailAddress 🔽
461	Help Method:	
	String:	<u> </u>
462	C Handler:	
463	Notes:	
	<u>0</u> K	<u>C</u> ancel <u>H</u> elp

Fig. 8




Fig. 9






Fig. 10

```
E031 Handler Custom Code
                                                                                                    X
 ථාන යන්නව පාටු
  extern RLSTATUS
                                                                                            (M)
  ND_CommandSNandler(cli_env *ptliknv, parambist *pParams, sbyte *pAuxBuf)
      RUTATEAR
                   status - OK;
                                                                                            Graeci)
      sbyte
                   *pValls
      parambeser 'pParambeserl:
                                                                                            (E)OTF
                   *pVal2 = DULL;
      *Byte
      parambeser *pParambeser2;
                                                                                            £2030
      /5 get required parameter */
      status - BCC_PB_RetrieveParam(pParams, NULL, aCommand3_KULL1, apParamDesc
      if ( OK != status )
          return(etatus);
      } else pVail = (sbyte*)(pPerseDescri**pValue);
      RCC_EXT_UniteSer(pfliTmv, kformandSHagRaquiredValue);
      RCC_EXT_WeiseSerLine(pClillno, pVall);
      /* get optional parameter */
      if (OK == DCC_DB_BecrievePeren(pPerens, NULL, aCommand3_NULL2, apPerenDes
          pVal2 = (sbyte*)(pParamDescr2->pValue);
          RCC_EXT_WriteStr(pCliTnv, RCommand3NsgOptionalValue);
RCC_EXT_WriteStrLine(pCliTnv, pVal2);
                                                                                D
G
 Esta en la consumer a 200 direction, proce 6001-600
```

Fig. 11


600





720\_

Fig. 14






Fig. 15